

電性回路示意圖

- 第一段: 2個C1-1
- 第二段: 2個C1-2
- 第三段: 2個C1-3
- 第四段: 2個C1-4
- 第五段: 2個C1-5
- 第六段: 2個C1-6
- 第七段: 2個C1-7
- 第八段: 2個C1-8
- 第九段: 2個C1-9
- 第十段: 2個C1-10
- 第十一段: 2個C1-11
- 第十二段: 2個C1-12



序號	品名	材質	規格	數量	備注
1	鐵面板	鐵(鍍藍鋅)	SSPC55-Y-12P	1PCS	
2	黑色推柄	POM	一片式	1PCS	
3	端子板	PBT+30%纖(防火)	藍色T=4.2	2PCS	
4	上蓋	不銹鐵	T=0.5	1PCS	
5	螺母	鐵(鍍鎳)	M2.6*5.0*2.0	2PCS	
6	螺絲	鐵(鍍鎳)	M2.6*12.5	2PCS	
7	端子	黃銅(鍍銀)	T=0.4	28PCS	

3				PRODUCT NAME	多路開關		
2				MODEL NAME	SSPC55S-2-2-12-B-Y(維特專用)		
1				APPROVED BY	CHECKED BY	DRAWN BY	
NO	DATE	DESCRIPTION					
DIMENSION	TOLERANCE	SCALE					
$l \leq 10$	± 0.2	UNIT	mm				
$10 < l \leq 30$	± 0.5	VER.					
$30 < l \leq 100$	± 1.0	DATE	2011-5-19				



一、推动式多路開關系列技術規格書

Slide Series Route Switches Technic Specifications

1.電氣性能 (Electrical Characteristic)					
序号	项目			特性	
1.1	額定功率 (Rated Power)			DC 30V 0.5A	
1.2	絕緣阻抗 (Insulation Resistance)			More than 100MΩ at DC500V	
1.3	耐電壓 (Withstand Voltage)			For 1 minute at:500V	
1.4	接觸電阻 (Contact Resistance)			Less than 30mΩ	
2.機械性能 (Mechanical Characteristics)					
2.1	每段行程 (Each point of travel)			3.5±0.5mm	
2.2	推動力矩 (Slide Torque)			1 to 2 section 1.0±0.5kg.cm over section 2.5±1.0 kg.cm	
2.3	軸的拉、押強度 (Pull-Push Strength)			6.0 Kgf.cm	
2.4	轉動止檔強度 (Rotational Stop-End Torque)			5.0 Kgf.cm	
2.5	焊錫耐熱性 (Resistance To Soldering Heat)			260±5°C at 5±1 seconds	
2.6	使用溫度範圍： (Used Temperature Range)			10°C ~ 70°C	
2.7	開關操作力 (Switch Action)			50~300gf.cm	
3.耐久性能 (Durability)					
3.1	回轉壽命 (Rotation Life)			10,000Cycles Min	
批 准			審 核		
				設 計	